

HEATED HOLDING CABINETS

CLIMATE SELECT

FULL • 3/4 SIZE • HALF SIZE • UNDER COUNTER

Climate Select cabinets feature a 4-gallon water reservoir with low water alarm for hours of uninterrupted service. Humidity is operator-controlled for maximum flexibility and maximum holding time.

Constructed of stainless steel inside-and-out. Pan supports are stainless steel. Features include fully insulated top, side, base and doors. Top mounted convection heating system produces uniform temperature distribution down both sides and features solid state controls with a temperature range of 70° to 215°F (21° to 102°C) with a digital display option. May be used as a proofer.

Standard features include field reversible, lift-off, self-closing hinges, magnetic door gasket and latch, cool-touch handles and turn-knob locking device, cove corners, front and rear pull grips, HD plate casters with 5" (127mm) rubber wheels.

Options include pass-thru models, left or right hand hinges, and glass doors.

SELECT SERIES



PASS-THRU
AVAILABLE

3/4 SIZE
AVAILABLE



HCSS74W12 shown with optional
Pass-Thru & Glass Doors

Accessories & Options page 15



FULL SIZE

Model	Slides	Capacity			Overall Dimensions (HxWxD)		Ship Wt.		Electrical		List Price US\$
		# Positions	# Shelves	SPC*G*	in.	mm.	lbs.	kilos	volts	amps	
HCSS74W12	U	34	12	4.5"	73.75 x 28.12 x 34.00	1873 x 714 x 863	373	159	120 208 240	20 20 20	\$ 7,899

Accessories & Options page 15



HALF SIZE

STACKABLE

Model	Slides	Capacity			Overall Dimensions (HxWxD)		Ship Wt.		Electrical		List Price US\$
		# Positions	# Shelves	SPC*G*	in.	mm.	lbs.	kilos	volts	amps	
HCSS44W6	U	16	6	4.5"	43.75 x 28.12 x 34.00	1354 x 714 x 863	247	107	120 208 240	20 20 20	\$ 5,699

Accessories & Options page 15



UNDER COUNTER

Model	Slides	Capacity			Overall Dimensions (HxWxD)		Ship Wt.		Electrical		List Price US\$
		# Positions	# Shelves	SPC*G*	in.	mm.	lbs.	kilos	volts	amps	
HCSS34W4	U	12	4	4.5"	33.62 x 28.12 x 34.00	1354 x 714 x 863	234	106	120 208 240	20 20 20	\$ 5,599



15-15P
120v, 15amp



15-20P
120v, 20amp



6-15P
208v/240v, 15amp

Dimensions nominal

Shipping Class #85

* Adjustable on 1.5" centers

Universal slides are adjustable

Additional shelves available

*Stacked cabinets are stacked at factory — may be stacked as a lower cabinet with Temper Select

Right-hand hinging standard — left-hand hinging available — specify when ordering

208v and 240v available

FOB Standex Dock